

Surface Mount Schottky Barrier Rectifier

Reverse Voltage - 20 to 200 V


Forward Current - 1.0 A

Features

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode









Absolute Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbols	DS12W	DS14W	DS16W	DS18W	DS110W	DS112W	DS115W	DS120W	Units					
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	40	60	80	100	120	150	200	V					
Maximum RMS voltage	V_{RMS}	14	28	42	56	70	84	105	140	V					
Maximum DC Blocking Voltage	V_{DC}	20	40	60	80	100	120	150	200	V					
Maximum Average Forward Rectified Current	$I_{F(AV)}$	1.0							A						
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	40				30				A					
Max Instantaneous Forward Voltage at 1A	V_F	0.55		0.70		0.85		0.90		V					
Maximum DC Reverse Current $T_a = 25^\circ C$ at Rated DC Reverse Voltage $T_a = 100^\circ C$	I_R	0.3 10			0.2 5		0.1 2		mA						
Typical Junction Capacitance ¹⁾	C_j	110		80						pF					
Typical Thermal Resistance ²⁾	$R_{\theta JA}$	115								°C/W					
Operating Junction Temperature Range	T_j	-55 ~ +125								°C					
Storage Temperature Range	T_{stg}	-55 ~ +150								°C					

1) Measured at 1MHz and applied reverse voltage of 4 V D.C.


2) P.C.B. mounted with 0.2 X 0.2" (5 X 5 mm) copper pad areas.

Fig.1 Forward Current Derating Curve

Fig.3 Typical Forward Characteristic

Fig.5 Maximum Non-Repetitive Peak Forward Surge Current

Fig.2 Typical Reverse Characteristics

Fig.4 Typical Junction Capacitance

Fig.6- Typical Transient Thermal Impedance



PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SOD123FL



The recommended mounting pad size



Marking

Type number	Marking code
DS12W	S12
DS14W	S14
DS16W	S16
DS18W	S18
DS110W	S110
DS112W	S112
DS115W	S115
DS120W	S120