

## DESCRIPTION

The GBLC03CW is an ultra low capacitance ESD and Surge Protector designed to provide electrostatic discharge (ESD) protection for high-speed data interfaces. GBLC03CW is designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4 ( $\pm 15\text{kV}$  air,  $\pm 8\text{kV}$  contact discharge), IEC 61000-4-4 (EFT, 40A 5/50ns), IEC 61000-4-5 (Surge, 10A 8/20 $\mu\text{s}$ ), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc.

GBLC03CW is in an SOD-323 package. The combined features of ultra-low capacitance and high ESD robustness make GBLC03CW ideal for applications where arrays are not practical. The low clamping voltage of GBLC03CW guarantees a minimum stress on the protected IC.

## ORDERING INFORMATION

- ✧ Device: GBLC03CW
- ✧ Package: SOD-323
- ✧ Marking: CA1
- ✧ Material: Halogen free
- ✧ Packing: Tape & Reel
- ✧ Quantity per reel: 3,000pcs


## FEATURES

- ✧ IEC61000-4-2 (ESD)  $\pm 15\text{kV}$  (air),  $\pm 8\text{kV}$  (contact)
- ✧ IEC61000-4-4 (EFT) 40A (5/50ns)
- ✧ IEC61000-4-5 (Surge) 10A (8/20 $\mu\text{s}$ )
- ✧ Protects one I/O line (bidirectional)
- ✧ Low operating and clamping voltage
- ✧ Low leakage current


## MACHANICAL DATA

- ✧ SOD-323 package
- ✧ Flammability Rating: UL 94V-0
- ✧ Packaging: Tape and Reel
- ✧ High temperature soldering guaranteed: 260°C/10s
- ✧ Reel size: 7 inch

## PIN CONFIGURATION



## PACKAGE OUTLINE












**ABSOLUTE MAXIMUM RATING**

Symbol	Parameter	Value	Units
$V_{ESD}$	ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	$\pm 15$ $\pm 8$	kV
$P_{PP}$	Peak Pulse Power (8/20μs)	150	W
$I_{PP}$	Peak Pulse Current (8/20μs)	10	A
$T_{OPT}$	Operating Temperature	-45 ~ +85	°C
$T_{STG}$	Storage Temperature	-55 ~ +150	°C


**ELECTRICAL CHARACTERISTICS (Tamb=25°C)**

Symbol	Parameter	Test Condition	Min	Typ	Max	Units
$V_{RWM}$	Reverse Working Voltage				3.3	V
$V_B$	Reverse Breakdown Voltage	$I_R = 1\text{mA}$	3.5			V
$I_R$	Reverse Leakage Current	$V_{RWM} = 3.3\text{V}$			500	nA
$V_{C1}$	Clamping Voltage 1	$I_{PP} = 1\text{A}, t_p = 8/20\mu\text{s}$			6.5	V
$V_{C2}$	Clamping Voltage 2	$I_{PP} = 10\text{A}, t_p = 8/20\mu\text{s}$			15.0	V
$C_{ESD}$	Parasitic Capacitance	$V_R = 0\text{V}, f = 1\text{MHz}$			1.0	pF

**ELECTRICAL CHARACTERISTICS CURVE**
**8/20 $\mu$ s Pulse Waveform**

**Clamping Voltage  $V_c$  vs. Current  $I_{PP}$** 

**Insertion Loss S21**

**Normalized Capacitance vs. Voltage**

**ESD Clamping of I/O to GND  
(+8kV Contact per IEC 61000-4-2)**

**ESD Clamping of I/O to GND  
(-8kV Contact per IEC 61000-4-2)**


**SOD-323 PACKAGE OUTLINE DIMENSIONS**


Symbol	Dimensions In Millimeters	
	Min	Max
A		1.00
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
e	1.800	2.040
L	0.475 REF	
L1	0.250	0.400
$\theta$	0°	8°


**Recommended Pad outline**